ULTRACARE MULTICLEANER

Concentrated neutral cleaner with a very high yield, ideal for daily cleaning and maintenance of surfaces, including marble and natural stones





BENEFITS AND FEATURES

- Cleans effectively and non-aggressively, respecting the material and any protector applied
- Indoor, outdoor, walls and floors
- High yield
- Biodegradability
- Highly concentrated (to be diluted)
- Dries without streaks
- Suitable for treated and untreated surfaces

CO_2e FULLY OFFSET PRODUCTS

Residual Greenhouse Gas emissions measured throughout the life cycle of this product using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset for the year 2026 through the acquisition of carbon credits in support of forestry protection projects. For more details on emission calculations and offsetting projects, visit mapei.com.

WHERE TO USE

Suitable for use on:

- marble, granite and all natural stones, perfect for use on polished natural stones that are sensitive to aggressive detergents;
- porcelain and ceramic tiles;
- concrete flooring;
- parquet with oil or paint finish;
- terrazzo and terracotta;
- quartz and marble agglomerates;
- flooring in LVT, linoleum, rubber and PVC;
- acrylic resin flooring created using **Mapecoat TNS** range.

PRODUCT INFORMATION

UltraCare Multicleaner is a concentrated cleaner. Its special formula guarantees a high level of cleanliness, respecting the surfaces on which it is used. It is suitable for use on all washable surfaces, including the most delicate ones, thanks to its neutral pH. It is also characterized by a pleasant scent.

UltraCare Multicleaner when diluted (1 : 200) does not require rinsing as it leaves no residues and/or halos on the surfaces and can be used both indoors and outdoors.

It is effective for ordinary and extraordinary maintenance operations, depending on the degree of dilution as detailed below.

Used regularly, it keeps colours vivid and retains the appearance of the surfaces on which it is used.

RECOMMENDATIONS

- **UltraCare Multicleaner** on waxed surfaces can be used only diluted.
- Do not use **UltraCare Multicleaner** undiluted.
- When using **UltraCare Multicleaner**, we advise wearing rubber gloves.
- Use on methacrylate baths only when diluted.
- **UltraCare Multicleaner** does not damage metal or galvanized surfaces.

APPLICATION PROCEDURE

Dilute **UltraCare Multicleaner** with water in a ratio from 1 : 20 to 1 : 200 depending on the degree of concentration required and the level of dirt to be removed.

UltraCare Multicleaner can be used diluted 1 : 30 to undertake the initial clean after installation on delicate surfaces.

For daily maintenance, dilute **UltraCare Multicleaner** 1 : 200 (50 ml of product in 10 litres of water). In this dilution, rinsing the treated surfaces is not necessary.

For extraordinary maintenance or more resistant dirt, use the product at higher concentrations up to 1 : 20 (500 ml of product in 10 litres of water). At these dilutions, it is necessary to rinse the surfaces with water.

You can use the product by altering the dilutions to those described above, making it adaptable to your specific needs. The surface must be rinsed when used in a dilution of less than 1 : 200. Please ensure that the surface is rinsed with plenty of clean water.

You can use **UltraCare Multicleaner** in floor-cleaning machines following the instructions of the machine manufacturers.

CONSUMPTION

Diluted in a ratio of 1 : 200 with water, it is possible to clean approximately 1500 m^2 of surface area with a litre of **UltraCare Multicleaner**. Consumption may vary based on dilution, the degree and type of dirt, and the surface to be treated.

PACKAGING

UltraCare Multicleaner is available in 1- and 5-litre jerrycans.

STORAGE

UltraCare Multicleaner, stored in the original packaging, has a storage time of 3 years.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found in the latest version of the Safety Data Sheet, available on our website at www.mapei.ae.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY	
Consistency:	liquid
Colour:	transparent
Density:	1.00 g/cm³
pH:	8
Recommended temperature range:	0°C to +40°C
Waiting time before rinsing:	5 minutes

IMPORTANT NOTES

While we try to ensure that any advice, recommendations, or information in our literature is accurate and correct, we have no control over the circumstances in which our product is used. It is, therefore, important that installers satisfy themselves that the product and conditions are suitable for the envisaged application. No warranty can be given, nor can responsibility be accepted, other than the product we supply will meet our written specifications. The installer should ensure that our latest product data and safety information sheets have been consulted before use.

Please refer to the current version of the Technical Data Sheet, available on our website www.mapei.ae.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into other project-related documents. The resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation. The most up-to-date TDS can be downloaded from our website, www.mapei.ae.

ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDE THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com.

Mapei Construction Chemicals L.L.C

Dubai Investment Park 2, P.O. Box: 73869, Dubai, United Arab Emirates

+971 4 815 6666 www.mapei.ae info@mapei.ae

11005-7-2026 (UAE)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution